

# TEOM 1405 Ambient Particulate Monitor

## Continuous measurement of ambient particulate concentrations

Ambient Particulate Monitor is the replacement for the successful Thermo Scientific TEOM 1400ab Ambient Particulate Monitor which is the choice of air pollution monitoring networks worldwide for the continuous measurement of particulate mass concentrations.

### Features

- U.S. EPA PM-10 Equivalent Monitor (EQPM-1090-079)
- Proprietary TEOM technology
- Touch screen user interface
- Embedded FTP server, ethernet, USB, RS232 and RS485 communications
- Activol flow control

### Introduction

The TEOM™ 1405 monitor has become the de facto standard for particulate mass concentration measurements in areas such as Canada, Hong Kong, the United Kingdom and France due to the high data quality, reliability and unparalleled support.



This instrument incorporates our proprietary tapered element oscillating microbalance, a microweighing technology that provides true mass measurements. Using a choice of sample inlets, the hardware can easily be configured to measure PM-10, PM-2.5, PM-1 or TSP concentrations. This single cabinet, network ready unit easily accommodates all site requirements and provides internal data storage and advanced analog and serial data input/output capabilities.

The TEOM 1405 monitor provides a self-referencing, NIST-traceable true mass measurement using our proven high-reliability proprietary TEOM technology.

The system differentiates itself from other PM measurement methods by utilizing a direct mass measurement that is not subject to measurement uncertainties found in surrogate techniques such as beta attenuation, light scattering and pressure drop.

Thermo Scientific™  
TEOM™ 1405 Monitor



## Thermo Scientific TEOM 1405 Ambient Particulate Monitor

Specifications	
Measurement range	0 to 1,000,000 µg/m <sup>3</sup> (1 g/m <sup>3</sup> )
Resolution	0.1 µg/m <sup>3</sup>
Precision	± 2.0 µg/m <sup>3</sup> (1-hour ave), ±1.0 µg/m <sup>3</sup> (24-hour ave)
Accuracy	Mass Measurement: ±0.75%
Real-time mass conc average	10 min default, 10 to 3600 sec
Long-term averaging	30 min, 1, 8 and 24 hr
Data output rate	Every 2 seconds
Operating range	The temperature of the sampled air may vary between -40 and 60 °C. The TEOM Sensor and Control Units must be weather protected within the range of 2 to 40 °C. An optional Complete Outdoor Enclosure provides complete weather protection.
Standard system configuration	Menu-driven software for user interaction via 1/4 VGA display with touch screen Connecting and Interface Cables, and Vacuum Pump Consumables for average first year's operation (ambient) RPCOMM and ePort software for local or remote communication
Sample flow	Activol flow control system uses the mass flow sensors and the measured ambient temperature and pressure to maintain constant volumetric flow rates. Main Flow Rate: 3 l/min, Bypass Flow Rate: 13.67 l/min
Main flow rate	3 l/min
Bypass flow rate	13.67/min
Data storage	Internal data logging of user-specified variables; capacity of 500,000 records.
Filter media	Sample Filter: Pallflex TX40, 13 mm effective diameter
Data output and input	ePort software to view and change system operation from PC Touch screen user interface Ethernet with embedded FTP server, USB, RS232, RS485, 8 User-Defined Analog Outputs (0-1 or 0-5 Vdc), 2 User-Defined Contact Closure Alarm Circuits, 4 Averaged Analog Inputs (0-5 Vdc) with user-defined conversion to engineering units
Power requirements	
Instrument	100-240 VAC, 440 VA, 47-63 H
Pump	120 VAC/60 Hz: 4.25 A; 240 VAC/50 Hz: 2.25 A
Physical dimensions	W: 17" (43.2 cm) × D: 19" (48.3 cm) × H: 29.5" (140 cm), (75 cm)
Weight	40 lbs (18 kg)
Safety/electrical designations	CE: EN 61326:1997 + A1:1998 + A2:2001 + A3:2003, EN:61010-1 UL: 61010-1:2004, CSA: C22.2 No. 61010-1:2004, FCC: Part 15 Subpart B, Class B
Approvals and certifications	U.S. EPA PM-2.5 Equivalent Monitor EQPM-0609-181 Candidate for U.S. EPA PM-10 and PM-2.5 Equivalent Monitor Candidate for TÜV PM-10 and PM-2.5 Equivalent Monitor

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific products.

### USA

27 Forge Parkway  
Franklin, MA 02038  
Ph: (866) 282-0430  
Fax: (508) 520-2800  
orders.aqi@thermofisher.com

### India

C/327, TTC Industrial Area  
MIDC Pawane  
New Mumbai 400 705, India  
Ph: +91 22 4157 8800  
india@thermofisher.com

### China

8/F Bldg C of Global Trade Ctr,  
No.36, North 3rd Ring Road,  
Dong Cheng District  
Beijing, China 100013  
Ph: +86 10 84193588  
info.eid.china@thermofisher.com

### Europe

Ion Path, Road Three,  
Winsford, Cheshire CW73GA UK  
Ph: +44 1606 548700  
Fax: +44 1606 548711  
sales.epm.uk@thermofisher.com

Find out more at [thermofisher.com](http://thermofisher.com)

**ThermoFisher**  
SCIENTIFIC